



Cygnus 4+ General Purpose Multi-Mode Ultrasonic Thickness Gauge

New generation of ultrasonic thickness gauges incorporating Multiple-Echo, Echo-Echo and Single-Echo measuring modes



"Simplicity through technology"

NEW CYGNUS 4+ GENERAL PURPOSE MULTI-MODE THICKNESS GAUGE

The NEW Cygnus 4+ is a small and tough multi-mode ultrasonic thickness gauge which features an A-scan display and simple to use sequential data logging.

Designed for the harshest of environments, with a simple to use keypad, intuitive menus and a colour LCD display which can be viewed in all lighting conditions.

The twin shot injection moulded enclosure has a soft but durable TPE outer skin which is comfortable to hold and protects against bumps while the hard internal shell offers maximum strength and environmental protection certified to the demanding US MIL STD 810G standard.

The unit still relies on Multiple-Echo to provide simple and accurate measurements, with the added benefit of Echo-Echo and Single-Echo using twin crystal probes for extreme corrosion. Echo-Echo for measurements on painted metals but with heavy back wall corrosion / pitting and Single-Echo for measurements on uncoated surfaces with heavy front face and/or back-wall corrosion and attenuative materials such as cast metals or plastics / composites.



KEY FEATURES

- Multiple-Echo for reliable, accurate through coating measurements
- Single-Echo and Echo-Echo measuring modes with twin crystal probes for extreme corrosion and back wall pitting
- A-scan display
- MSI™ (Measurement Stability Indicator) used in Single-Echo and Echo-Echo measurement modes
- Simple linear data logging
- Large bright colour LCD screen with back light
- Deep-coat mode, measure through coatings up to 20 mm thick
- Wrist mountable
- Min/max measurement limit functions with visual and vibrate alert
- Intuitive easy to use menu
- Extremely rugged enclosure – shock and impact to US MIL STD 810G
- Environmental sealing to IP67 – US MIL STD 810G
- Cygnus echo strength bars to assist quick measurements
- Buttons integral with the TPE moulding and designed for minimum 100,000 depressions.

DATA LOGGING KEY FEATURES

- Versatile data logging which allows measurements and A-scans to be saved
- 5,000 measurement points (including A-scan) per record
- Records are saved to a removable SD card
- Selectable auto-log feature
- Records easily transferred via gauge USB port to Cyglink software where they can be exported to a CSV file or a PDF report.

All Cygnus thickness gauges are supplied with a 3 YEAR Cygnus Gauge Warranty as standard



SPECIFICATION

Materials	Sound velocities between 1,000 m/s - 9,000 m/s - covers virtually all common engineering materials		
Accuracy	±0.1 mm or 0.1% of thickness measurement, whichever is greatest, when calibrated in accordance with Cygnus Instruments calibration procedure		
Resolution	Multiple-Echo mode - 0.1 mm or 0.05 mm Single-Echo and Echo-Echo modes - 0.01 mm		
Probes	Single crystal probes: • 6 mm - 5 MHz (S5A) • 13 mm - 2.25 MHz (S2C (standard)), 3.5 MHz (S3C) or 5 MHz (S5C) • 19 mm - 2.25 MHz (S2D)	Twin crystal probes: • 5 mm - 7.5 MHz (T7A) • 8 mm - 5 MHz (T5B (standard)) • 13 mm - 2 MHz (T2C (for attenuative materials such as cast metals, plastics and composites))	
Measurement Range in Steel	Single crystal probes: • 3 mm - 250 mm with 2.25 MHz probe (S2C/D) • 2 mm - 150 mm with 3.5 MHz probe (S3C) • 1 mm - 50 mm with 5 MHz probe (S5C/A)	Twin crystal probes in Single-Echo: • 2 mm - 250 mm with 2 MHz probe (T2C) • 1.5 mm - 200 mm with 5 MHz probe (T5B) • 0.7 mm - 50 mm with 7.5 MHz probe (T7A)	Twin crystal probes in Echo-Echo: • 5 mm - 50 mm with 2 MHz probe (T2C) • 4 mm - 50 mm with 5 MHz probe (T5B) • 3 mm - 25 mm with 7.5 MHz probe (T7A)
Connector	Twin Lemo 00		
Power	3 x AA batteries		
Battery Life	10 hours minimum		
Electronics	Dual channel pulser		
Display	2.4" quarter VGA LCD		
Size	132 mm x 82 mm x 34 mm		
Weight	300 grams (inc. batteries)		
Operating Temp.	-10°C to 50°C		
Data Logging	Capacity for up to 5000 points including A-scans		
Computer Software	CygLink allows remote logging and viewing of A-scan graphs. Survey and report generation to PDF file. Graphic analysis of data and statistical calculations. Designed for Windows 7 and Windows 8.		
Environmental Rating	IP67 Explosive Atmosphere: Safe operation as defined by Class I, Division 2, Group D, as found in the National Fire Protection Association Code (NFPA 70), Article 500, and tested using MIL STD 810G Method 511.5, Procedure I MIL STD 810G Method 501.6 (high temp +55°C) MIL STD 810G Method 502.6 (low temp -20°C) MIL STD 810G Method 507.6 (humidity 95%) MIL STD 810G Method 512.6 (immersion - 1 metre for 30 mins)		
Shock and Impact	MIL STD 810G Method 514.7 (vibration - 1 hour each axis) MIL STD 810G Method 516.7 (shock 20g - 11ms half sine shock pulse, 40g 11ms in each axis) MIL STD 810G Method 516.7 (26 drops - transit drop 1.22 m)		
Compliance	CE, British Standard BS EN 15317:2013 (specification for the characterisation and verification of ultrasonic thickness measuring equipment)		
Environmental	RoHS, WEEE compliant		
Warranty	3 years on gauge and 6 months on probe		

**Specifications are subject to change*

CYGNUS REGIONAL OFFICES

Cygnus Headquarters

Cygnus Instruments Ltd
 Cygnus House
 30 Prince of Wales Road
 Dorchester
 Dorset DT1 1PW
 United Kingdom

T: +44 (0) 1305 265 533
 E: sales@cygnus-instruments.com
 W: www.cygnus-instruments.com

Cygnus USA

Cygnus Instruments Inc.
 PO Box 6417
 Annapolis
 MD 21401
 USA

T: +1 (410) 267 9771
 E: sales@cygnusinstruments.com
 W: www.cygnusinstruments.com

Cygnus UAE

Cygnus Instruments Middle East
 P.O. Box 127267
 Jebel Ali Free Zone (JAFZA)
 Dubai
 UAE

T: +971 50 3459305
 E: ribu@cygnus-instruments.com
 W: www.cygnus-instruments.com

Cygnus Singapore

Cygnus Instruments (S) Pte Ltd
 63 Jalan Pemimpin #05-01
 Pemimpin Industrial Building
 577219
 Singapore

T: +65 6252 5909
 E: sales@cygnus-instruments.sg
 W: www.cygnus-instruments.sg

