

Jupiter



Radio module for the LoRa DeepWave system: ePaper wide screen (like the one of ebooks), 2 inputs for Smart Sensor chosen from those available (temperature, humidity, differential pressure, light), local acoustic alarms through a buzzer. The **Smart Sensors** (not included) are supplied with an **reference traceable calibration certificate** and allow fast, economic and easy recalibration of the whole system, without external intervention. Jupiter mounts external antenna and external power also (batteries are used as a backup). DeepWave solution is based on the Lo.Ra. (Long Range) radio protocol which allows transmission over very long distance and requires only one Helios receiver to cover all nodes. Batteries are easily replaceable by the user.



Main features

- Lora radio module for long distances transmission (up to 3 km in open field)
- Supports up to two Smart Sensors of temperature, humidity, differential pressure, light
- 2.9" wide ePaper display
- External power connector (power adapter not included)
- External antenna included
- 4-buttons for display screen scrolling
- User replaceable batteries
- Certificate traceable to a national standard included with the Smart Sensors

Plus

- Easy to install and configure
- Quick recalibration with the Smart Sensors
- With the external antenna you increase the transmission by 50%
- Wide and low energy display
- Local alarm for immediate intervention
- Thanks to the external power you forget to change the batteries
- Covers long transmission distances
- Validatable DeepWave LoRa system in pharmaceutical and healthcare environment

The system

Lora Wan DeepWave system is made up by:

- DeepWave radio modules (Lo.Ra. nodes)
- Helios receiver (Lo.Ra. gateway)
- TSLog 21 software

Accessories

- TSLog 21
- Helios - LoRa Gateway
- Surface Support for DeepWave Node
- Wall Mounting support for DeepWave Node
- Temperature Smart Sensor
- -80°C temperature Smart Sensor
- 200 temperature Smart Sensor

Applications



Pharmaceutical



Healthcare



Cosmetics



Validation



Medical



Cold Chain



Warehouses



Environment



Food & Beverages



Laboratories



Constructions

- Temperature Smart Sensor with thin cable
- Temperature and humidity Smart Sensor
- Differential Pressure Smart Sensor
- Light Smart Sensor (On/Off)
- Temperature Smart Sensor with internal sensor
- Smart Sensor / ZED IT adapter cable extensions
- Flat DeepWave Node / Smart Sensor cable extension
- LoRa Node / Smart Sensor cable extensions

Technical specifications

Dimensions	146.6 X 88 X 33 (mm)
Weight	280 g
Materials	ABS, Rubber
Sensors	2 X Smart Sensor inputs
Temperature range	-20 °C ÷ +50 °C
Memory (n. of acquisitions)	16.383
Acquisition step	From 1 minute up (in steps of 1 minute)
Display size	
Display and functions	Current values, Alarms, Diagnostics, Radio Signal Strength
Alarms	Local (acoustic)
Functions	Data recording, transmission, alarm
Communication	Radio
Protocollo Radio	Lo.Ra.
Frequenza	868 MHz
Antennae	External
Battery type	3 AA 1,5 V batteries
Battery life	18 months with 15 minutes transmission step
Power supply	6-26 V (adapter not included)
Protection degree	IP65
Software&Mobile App	TSLog 21
Regulation compatibility	CE, ROHS
Regulation compatibility	FDA 21 CFR Part 11, Annex 11, GAMP 5